

In this Edition:

- Tip of the Month
- BOP Handling Systems
- Environmentally friendly JDN Air Hoists

Tip of the Month

Now available: The new JDN Air Hoists PROFI 1.5 TI and PROFI 3 TI / 2.

BOP Handling Systems



Convincing Features:

- Carrying capacities: 20 t - 200 t
- Pneumatic or hydraulic drive
- Standards: API 7K, ABS, ANSI B30.16, DNV Approval Programmes, NORSOK
- Tensile strength 2.5
- Dynamic factor 1.33
- Safety factor 5:1
- Traceability by JDN unique parts marking system
- Overload adjustable from 90% to 125%
- 3.1B Certification on load carrying parts
- Worldwide service

Can hoists be environmentally friendly?

Of course they can. That is why the environmentally conscious management is a fundamental component of the corporate policy at J.D. Neuhaus.

Starting with the development and production of our products, we place great value on ecological compatibility. Long service life and recyclability already make an important contribution towards relieving the environmental burden.

Furthermore our production facilities have been adapted to minimise energy consumption, emissions, sewage and waste. Environmentally friendly production processes and materials are also employed.



JDN Production

One of the most important commitments of the J.D. Neuhaus management is to promote awareness, openness and a sense of responsibility among employees in order to establish conditions favourable to the implementation of our environmental guidelines.



PROFI 1.5 TI

PROFI 3 TI / 2

In addition JDN Products can be oil-free operated due to the self-lubricating motor. That results in zero lubricant emission. Sound pressure levels and air consumptions will be minimised continuously.



JDN Rotor with grease chambers



JDN Environmental Guidelines

The certification process for our Environmental Management System acc. to ISO 14001 is already running at full speeds and the approval will take place end of the year.

Questions regarding this newsletter may be forwarded to: info@jdn.com.sg.

Your J.D. NEUHAUS Sales Team